

The LANL nEDM Experiment

Takeyasu Ito
Los Alamos National Laboratory

August 1, 2022
ECT* workshop | Neutron Electric Dipole Moment: from theory to experiment

Outline

- Purpose and goal
- UCN source and its upgrade
- nEDM experiment overview
- North Beamline characterization
- Vacuum chamber
- Magnetically shielded room
- B0 coil
- Magnetometry
- Status and plans

LANL nEDM Collaboration

T. Chupp*, S. Clayton, C. Cude-Woods, S. Currie, T. Hassan, T. Ito, M. Makela, C. Morris,
C. O'Shaughnessy, Z.Tang, W. Uhrich, A. Urbaitis,

Los Alamos National Laboratory

** 2020 LANL Rosen scholar*

T. Chupp, F.B. Hills

University of Michigan

N. Sachdeva

Northwestern University

J. Chen, F. Gonzales, C. Hughes, C.-Y. Liu, J. Long, A. Reid, W. Snow, D. Wong

Indiana University

J. Brewington, W. Korsch, M. McCrea, P. Palamure, B. Plaster, A. Tewsley-Booth

University of Kentucky

R. Pattie Jr.

East Tennessee State University

A. Holley

Tennessee Tech University

S. Stanislaus

Valparaiso University

T. J. Bowles, B. Heckel

University of Washington

S.K. Lamoreaux

Yale University

E. Sharapov

Joint Institute of Nuclear Research




Northwestern



LANL nEDM: concept

- A neutron EDM experiment with an uncertainty of $\delta d_n \sim O(10^{-27})$ e-cm based on proven room temperature Ramsey's separated oscillatory field method could take advantage of the existing LANL SD2 UCN source.
- nEDM measurement technology for $\delta d_n \sim O(10^{-27})$ e-cm already exists. The systematic uncertainty of the recent PSI results was 2×10^{-27} e-cm.
- The successfully upgraded LANL UCN source has been shown to provide the UCN density required for an nEDM experiment with $\delta d_n \sim O(10^{-27})$ e-cm.
- Such an experiment could provide a venue for the US nEDM community to obtain physics results, albeit less sensitive, in a shorter time scale while development for the nEDM@SNS experiment continues.

nEDM measurement principle



$$\nu = (2\mu_n B \pm 2d_n E) / h$$



$$\Delta\nu = 4d_n E / h$$

$$\delta d_n = h \frac{\delta\Delta\nu}{4E}$$

For $B \sim 1 \mu\text{T}$, $\nu = 30 \text{ Hz}$.


For $E = 10 \text{ kV/cm}$ and $d_n = 3 \times 10^{-27} \text{ e-cm}$, $\Delta\nu = 0.03 \mu\text{Hz}$.

Ramsey method of separated oscillatory fields




Baker et al, NIMA 736, 184 (2014) (arXiv:1305.7336)

Los Alamos Neutron Science Center (LANSCE)



CIC-9: RN91-240-309

LANL UCN Experimental Area




LANL UCN Experimental Area

UCN source

UCN τ /UCN τ^+ experiment

Helium liquefier




MSR for LANL
nEDM experiment


UCNA/UCNB/UCNA+ experiment




LANL UCN source




Spallation neutrons from W target
K.E. ~ 2 MeV



Thermal neutrons in Be and graphite moderator
K.E. ~ 25 meV




Cold neutrons in polyethylene cold moderator
K.E. ~ 6 meV



Ultracold neutrons in SD2 converter
K.E. ~ 100 neV

UCN density (UCN/cm³)





An upgrade of the UCN source (FY14-17) more than quadrupled the UCN output by:

1. increasing the average beam current
2. replacing the UCN source insert with one optimized for CN moderation and UCN transport.

[Ito et al. PRC 97, 012501(R) (2018).]




UCN density measurement based on vanadium activation



- Detecting the 1.4 MeV gammas with a Ge detector determines the UCN capture rate by the vanadium foil.
- The Ge detector can be calibrated (for the efficiency and solid angle product) by placing a calibrated ${}^{60}\text{Co}$ source at the location of the vanadium foil.
- UCN density can be determined from:

$$R = \frac{1}{4} v A \rho$$

Polarized UCN density in a dummy nEDM cell on the West Beamline



Polarized UCN density ($E < 170$ neV) at $t=0$

- 12 UCN/cc from the fill and dump measurement (was 2.5 UCN/cc before the source upgrade)
- 36 UCN/cc from vanadium foil activation measurement

The difference can be attributed to loss in the switcher and the finite detection efficiency.

Estimated statistical sensitivity of an nEDM experiment

Parameters	Values
E(kV/cm)	12.0
N(per cell)	39,100
T _{free} (s)	180
T _{duty} (s)	300
α	0.8
σ/day/cell (10 ⁻²⁶ e-cm)	5.7
σ/day (10 ⁻²⁶ e-cm) (for double cell)	4.0
σ/year (10 ⁻²⁷ e-cm) (for double cell)	2.1
90% C.L./year (10 ⁻²⁷ e-cm) (for double cell)	3.4



This estimate is based on the following:

- The estimate for E, T_{free}, T_{duty}, and α is based on what has been achieved by other experiments.
- The estimate for N is based on the actual detected number of UCN from our fill and dump measurement at a holding time of 180 s. **Further improvements are expected (new switcher and new detector).**

$$\delta d_n = \frac{\hbar}{2\alpha E T_{\text{free}} \sqrt{N}}$$

* “year” = 365 live days. In practice, it will take 5 calendar years to achieve this with 50% data taking efficiency

Neutron transport and storage test on the North beam line





Measurement corresponds to ~60,000 detected UCN @ 2000 Hz GV rate after 180 s when a dPS coated cell wall was used with the new switcher


Apparatus overview

TA-53 Area B (UCN Experimental Hall)

LANL nEDM experiment




Overall design of the experiment



Selected features:

- Ramsey's separated oscillatory field method at RT.
- Double precession chamber.
- Simultaneous spin analysis
- MSR:
 - 4 layer mu-metal + 1 layer RF shield
 - Outer dimension: 3.5 m x 3.5 m x 3.5 m
 - Inner dimension: 2.4 m x 2.4 m x 2.4 m
- Magnetometry:
 - ^{199}Hg comagnetometer
 - ^{199}Hg external magnetometer inside the HV electrode
 - Atomic external magnetometers
- Demonstrated UCN density
- Sensitivity goal: $\delta d_n \sim 3 \times 10^{-27}$ e-cm in one live year


Overall design of the experiment



Selected features:

- Ramsey's separated oscillatory field method at RT.
- Double precession chamber.
- Simultaneous spin analysis
- MSR:
 - 4 layer mu-metal + 1 layer RF shield
 - Outer dimension: 3.5 m x 3.5 m x 3.5 m
 - Inner dimension: 2.4 m x 2.4 m x 2.4 m
- Magnetometry:
 - ^{199}Hg comagnetometer (initially we will run without it)
 - ^{199}Hg external magnetometer inside the HV electrode
 - Atomic external magnetometers
- Demonstrated UCN density
- Sensitivity goal: $\delta d_n \sim 3 \times 10^{-27}$ e-cm in one live year

Overall design of the experiment





Selected features:


- Ramsey's separated oscillatory field method at RT.
- Double precession chamber.
- Simultaneous spin analysis
- MSR:
 - 4 layer mu-metal + 1 layer RF shield
 - Outer dimension: 3.5 m x 3.5 m x 3.5 m
 - Inner dimension: 2.4 m x 2.4 m x 2.4 m
- Magnetometry:
 - ^{199}Hg comagnetometer (initially we will run without it)
 - ^{199}Hg external magnetometer inside the HV electrode
 - Atomic external magnetometers
- Demonstrated UCN density
- Sensitivity goal: $\delta d_n \sim 3 \times 10^{-27}$ e-cm in one live year

UCN transport (LANL, Indiana)

Neutron switcher




UCN transport





Switchers being installed

Vacuum chamber and internal design



Non-magnetic vacuum chamber

Electrodes and precession chamber





Ground electrode

Precession chamber walls: dPS coated PMMA
Electrodes: NiMo coated aluminum -> DLC coated aluminum


UCN valves

- Valve box similar to a gate valve
- Slides between transport section and valve plug
- Valve plug closes on a linkage
- Components have been fabricated and test fit



Magnetically shielded room (LANL, Indiana U.)


4 μ -metal + 1 Cu layers




Design performance

Frequency (Hz)	SF
0.01	100,001
0.1	100,001
1	1,000,001
10	10,000,001
100	10,000,001


Magnetically shielded room



Field cage: MSR evaluation and cancellation of external fields




Shielding factor





B0 coil design (U. Kentucky)

- Octagon-shaped multi-gap solenoid
- Spin-transport coil interface


- Modelled gradient: $\left| \frac{\partial B_z}{\partial z} \right| < 0.1 \text{ nT/m}$
- Specifications: $\left| \frac{\partial B_z}{\partial z} \right| < 0.3 \text{ nT/m}$ inside each cell (the difference between the cells $< 10 \text{ pT}$)



Spin-Transport coils
Double Layer Modified Cos θ



Half scale B0 coil prototype tested inside an MSR



Half scale B0 coil prototype tested inside an MSR





- Tuning the current ratio between outer and inner coil sections to make $\frac{\partial B_z}{\partial z}$ gradient smaller
- Change the current in the z shim coil to fine tune the $\frac{\partial B_z}{\partial z}$ gradient further

Tuning current ratio with $B_0 \cong 2.9 \mu\text{T}$, $I_{inner} = 100 \text{ mA}$

$I_{shim} = 100 \text{ mA}$


Tuning shim coil current with $B_0 \cong 2.9 \mu\text{T}$, $I_{inner} = 100 \text{ mA}$

$I_{outer}/I_{inner} = 1.71$




B0 coil status (U. Kentucky)

- The full scale B0 coil has been installed in the MSR.
- The work to characterize the performance of the B0 coil is on hold to give priorities to other tasks.




Magnetometers (U. Michigan)




Up to 13 external magnetometers (inside vacuum) monitor B_0 , gradients



OPMs: optically pumped alkali (Cs, Rb) magnetometers




Nuclear spin magnetometers: Hg, ^3He (UM/Twinleaf)



Hg-199 as co-magnetometer and magnetometers (Indiana U, UW)



- nEDM@LANL has two precession chambers.
- Hg atoms are optically pumped in the polarizing chamber and then are transferred to the precession chamber to monitor the magnetic field.
- 5 Hg magnetometers (HgMs) are inside the HV electrode.
- All the pump beams come in from the side of MSR.
- The laser beams for the top precession chamber and the pumping chambers will raise up to 7.6 ft and 6.2 ft from the optic table.
- The HgM cell is currently in experimental development.





Installation platform (Indiana U.)

- To be delivered to LANL early August



Status and plans

- MSR was delivered in January 2022. It meets performance requirements. More detailed characterization is necessary.
- nEDM apparatus is being assembled.
- We plan to start an engineering run this summer.
 - We will start with confirming UCN transport and storage.