Hadron-Argon Scattering Measurements at ProtoDUNE-SP

Richard Diurba (University of Bern) for the DUNE Collaboration

Presentation Based on:

- Kaon-Argon Publication <u>2408.00582</u> (Accepted by *PRD*)
- <u>NP04 2024 Report</u> for Activities at ProtoDUNE
- Updates from ICHEP 2024 (<u>Parallel Talk</u>, <u>Poster</u>)



What is the point of a test beam?



Nucleon multiplicities for pion absorption on carbon

Cross Sections in a Liquid argon Time Projection Chamber

 All analyses use some version of the thin-slice equation pioneered by LArIAT (<u>*Phys. Rev. D* 106</u>, 052009):

$$N_{\rm inc.} - N_{\rm int.} = N_{\rm inc.} \exp\left(-\sigma r_{\rm trk.pitch} n\right) = N_{\rm inc.} \exp\left(-\frac{\sigma \rho_{\rm Ar} r_{\rm trk.pitch} N_{\rm avo.}}{M_{\rm Ar}}\right)$$

$$\sigma \left(\mathrm{KE} \right) = \frac{\mathrm{M}_{\mathrm{Ar}}}{\mathrm{N}_{\mathrm{avo.}} \mathrm{r} \rho} \mathrm{ln} \left[\frac{\mathrm{N}_{\mathrm{inc.}} (\mathrm{KE})}{\mathrm{N}_{\mathrm{inc.}} (\mathrm{KE}) - \mathrm{N}_{\mathrm{int.}} (\mathrm{KE})} \right]$$

Constants used:

- n: number density
- M_{Ar}: mass of argon nucleus
- N_{Avo.:} Avogadro's number
- r: pitch between wires
- ρ: liquid argon density



ProtoDUNE at CERN

- Two cryostats constructed at Neutrino Platform 2 and Neutrino Platform 4.
 - ProtoDUNE Single-Phase (ProtoDUNE-SP) ran at Neutrino Platform 4.
 - ProtoDUNE Dual-Phase (ProtoDUNE-DP) ran at Neutrino Platform 2.
- ProtoDUNE Horizontal Drift, successor of ProtoDUNE-SP, is operating and took beam data in summer 2024.
- ProtoDUNE Vertical Drift, successor to ProtoDUNE-SP, will operate late 2024 and early 2025.



ProtoDUNE-SP Results

- ProtoDUNE-SP has published six papers on its performance:
 - Detector physics (<u>JINST 15 P12004</u>)
 - Design and operation (<u>JINST 17 P01005</u>)
 - Michel electron reconstruction (*Phys. Rev. D* 107, 092012)
 - Reconstruction of cosmic/beam using Pandora (<u>EPJC 83 618</u>)
 - Track/shower separation using a CNN (<u>EPJC 82 903</u>)
 - Scintillation light detection with xenon-doping (<u>JINST 19 P08005</u>)



Resolution of reconstructing the energy of a Michel electron using various method with calibration taken from <u>JINST 15 P12004</u> (<u>Phys. Rev. D 107, 092012</u>) DUNE:ProtoDUNE-SP Simulation







Hadron Beam Taken at ProtoDUNE-SP

- Uses a tertiary hadron beam from CERN SPS (*Phys. Rev. Accel. Beams* 22, 061003).
- Beamline instrumentation provides tracking, PID, and momentum measurements (<u>JINST 15 P12004</u>).
- Beamline instrumentation tracking cross-checks tracking of Pandora-reconstructed beam candidate (<u>EPJC 83 618</u>).

(Right) Time-of-flight information measured by the beamline information system. Cherenkov detectors used when TOF overlap.





Event Selection of any Hadron Cross Section

Event Selection:

- Beamline instrumentation identifies hadrons with Cherenkov detectors and/or TOF.
- Reconstruction (EPJC 83 681) selects a TPC track.
- The TPC track must agree with beamline instrumentation tracking information.

$$N_{\text{inc.}} - N_{\text{int.}} = N_{\text{inc.}} \exp\left(-\sigma r_{\text{trk.pitch}} n\right) = N_{\text{inc.}} \exp\left(-\frac{\sigma \rho_{\text{Ar}} r_{\text{trk.pitch}} N_{\text{avo.}}}{M_{\text{Ar}}}\right)$$
$$\sigma\left(\text{KE}\right) = \frac{M_{\text{Ar}}}{N_{\text{avo.}} r \rho} \ln\left[\frac{N_{\text{inc.}} (\text{KE})}{N_{\text{inc.}} (\text{KE})}\right]$$



ProtoDUNE-SP Hadron Cross Sections in a Time Projection Chamber

 All analyses use some version of the thin-slice equation pioneered by LArIAT (<u>*Phys. Rev. D* 106, 052009</u>):

$$N_{\rm inc.} - N_{\rm int.} = N_{\rm inc.} \exp\left(-\sigma r_{\rm trk.pitch} n\right) = N_{\rm inc.} \exp\left(-\frac{\sigma \rho_{\rm Ar} r_{\rm trk.pitch} N_{\rm avo.}}{M_{\rm Ar}}\right)$$

$$\sigma \left(\mathrm{KE} \right) = \frac{\mathrm{M}_{\mathrm{Ar}}}{\mathrm{N}_{\mathrm{avo.}} \mathrm{r} \rho} \mathrm{ln} \left[\frac{\mathrm{N}_{\mathrm{inc.}} (\mathrm{KE})}{\mathrm{N}_{\mathrm{inc.}} (\mathrm{KE}) - \mathrm{N}_{\mathrm{int.}} (\mathrm{KE})} \right]$$

Constants used:

- n: number density
- M_{Ar}: mass of argon nucleus
- N_{Avo.:} Avogadro's number
- r: pitch between wires
- ρ: liquid argon density



Event Display of Kaon-Argon Interactions



Kaon Cross Sections According to Geant4



Reconstructed Distributions with Event Selection



Purities and Efficiencies of the Event Selection



First DUNE Result



Pion Exclusive Cross Section Measurements

- Investigating using a likelihood fitter to measure exclusive cross sections simultaneously.
- Additional event selection steps added to locate protons and neutral pions in event selection.

$$-2\log(L) = 2\sum_{j} \left(\beta_j N_j^{\mathrm{MC}} - N_j + N_j \log \frac{N_j}{\beta_j N_j^{\mathrm{MC}}} + \frac{(\beta_j - 1)^2}{2\sigma_j^2}\right)$$



Multi-Dimensional Unfolding



From Yinrui Liu's ICHEP 2024 Poster with method discussed in Instruments 8 (2024) 15.

Pion Inclusive Cross Section Measurements



Proton Inclusive Cross Section Measurements



Proton High-Energy Measurement

• Investigating high-energy tail of the cross section with a measurement of 572.64 millibarns.



Conclusion

- ProtoDUNE-SP is an advanced liquid argon time projection chamber with our first paper finished!
- After first analyses in 2024 and 2025, we will shift towards exclusive measurements, such as:



Exclusive cross section of the angle of the neutral pion scattering angle for a specific region of positively-charged pion kinetic energy. (K. Yang thesis)

- ProtoDUNE Horizontal Drift took data this summer with:
 - Positive and negative polarity data (positively and negatively charged pions and kaons!).
 - Oriented in a better way to probe pion resonance peak.

Pion Cross Sections with ProtoDUNE

• Better capabilities of probing the delta resonance of pions, the relevant region for DUNE!



Thank You!



Backup Slides

ProtoDUNE-SP Beam Event Displays



Response Matrices for the K+ Measurement

- Systematic uncertainties were developed to handle: mismodeling of the detector, calorimetry, beamline momentum resolution, and signal purity.
 - First usage of DUNE technologies for a full physics measurement.
- Unfold distributions using Bayes-like (Lucy-Richardson) unfolding with purity and eff. corrections (<u>NIMA 362 487</u>)



Test Beam Kinetic Energy Distribution for Kaons



Kinetic Energy Resolution for Kaons



Uncertainties of K+ Cross Section Study

Uncertainty Source $\begin{pmatrix} +1\sigma \\ -1\sigma \end{pmatrix}$	4480-5080 MeV (%)	5080-5340 MeV (%)	5340-5610 MeV (%)	5610-6170 MeV (%)
Beam modeling	-1.79 1.58	$2.50 \\ -3.89$	$\begin{array}{c}-0.74\\1.71\end{array}$	$4.01 \\ 0.51$
dE/dx calibration	$0.94 \\ 1.59$	$-0.71 \\ -0.76$	$-0.96 \\ -1.69$	$1.92 \\ 1.66$
Space charge effect	$1.28 \\ 1.92$	-1.18 0.76	-2.04 0.28	$2.05 \\ 4.42$
Geant4 modeling	$\begin{array}{r} 6.84 \\ -4.60 \end{array}$	$3.72 \\ -5.60$	$\begin{array}{c} 1.98 \\ -5.16 \end{array}$	$4.32 \\ -0.64$
Electron diverter effect	$\begin{array}{r} 6.54 \\ -1.24 \end{array}$	$3.11 \\ -2.68$	$1.64 \\ -2.73$	$2.42 \\ 3.43$
Vertex identification	$8.55 \\ -6.25$	$9.37 \\ -10.57$	$7.93 \\ -10.18$	$13.44 \\ -8.28$
Events without a track	$1.61 \\ 1.22$	$-0.29 \\ -1.40$	$-1.05 \\ -1.83$	$2.70 \\ 1.27$
Simulation statistics	-0.90 0.89	$-1.81 \\ 2.12$	$-1.54 \\ 1.76$	-2.27 2.48
Data statistics	$2.65 \\ -2.27$	-4.80 -9.77	$5.35 \\ -0.06$	
All Uncertainties	13.38 8.82	12.08 16.38	$10.35 \\ 12.25$	$16.88 \\ 10.56$

E-Slice Method of Thin-Slice Approach Traditional Thin-Slice Method (counts wires, strips, or other arbitrary volumes)

$$\sigma(E_{\rm kin}) = \frac{M_{\rm Ar}}{N_{\rm A}r\rho} \ln \left[\frac{N_{\rm inc}(E_{\rm kin})}{N_{\rm inc}(E_{\rm kin}) - N_{\rm int}(E_{\rm kin})}\right]$$

E-Slice Thin-Slice Method (counts number of times a particle has "enters an energy bin"

$$\sigma(E) = \frac{N_{\text{interaction}}(E)}{nN_{\text{end}}(E)\delta E} \frac{dE}{dx}(E) \ln\left(\frac{N_{\text{incident}}(E)}{N_{\text{incident}}(E) - N_{\text{end}}(E)}\right)$$

Deep Underground Neutrino Experiment (DUNE)

- A future long-baseline neutrino oscillation experiment to measure:
 - $\circ\;$ the mass hierarchy of neutrinos
 - $\circ~$ the CP-violating phase in the leptonic sector.
- Will use a muon (anti)neutrino beam (1.2 MW, can be 2.1 MW) with GeV-scale neutrino energies.
 - $\circ~$ Plans for four 17.5 kT liquid argon detectors at the Far Detector.
 - o Multi-target (LAr, Iron, H) Near Detector at Fermilab.
- Additional physics measurements requiring advances in detector performance:
 - o Atmospheric neutrinos
 - $\circ~$ Solar and supernova neutrinos
 - $\circ~$ Searches for proton decay
 - $\circ~$ Searches for boosted dark matter
 - $\circ~$ And much more!



Detector Layout at ProtoDUNE

- Largest monolithic LArTPC (700 tons)
- ProtoDUNE-SP has two drift volumes:
 3.6 m long drift volumes
- Electrons drift horizontally in the x-direction, beam travels in a slight angle primarily in the z-direction.



Diagram of APA wire planes used for readout. The diagram is rotated by 90 degrees clockwise from how it is installed to improve visualization.





Technical drawing of ProtoDUNE-SP. Three additional APAs are on the other side of the CPA.

> Image of CERN Neutrino Platform 4 with ProtoDUNE-SP. The beam comes in from left to right into the cryostat. The hanging scintillator in grey are the front Cosmic Ray Taggers.

Liquid Argon Time Projection Chambers (TPCs)

- Detector Physics to Consider:
 - Purity of liquid argon
 - o Uniformity of electric field
 - Surface-based detectors impacted by space charge on TPC walls.
 - $\circ~$ Efficiency of light detection
 - $\circ~$ Field response of the sensors
 - Electronics response
- France is pioneering the Vertical Drift:
- an alteration of this technology with strips.



Example of a liquid argon detector with a wire-based readout (arXiv:2002.03005).

Summary of ProtoDUNE-SP Detector Physics

- DUNE is the future US-based neutrino oscillation experiment specializing in liquid argon.
- ProtoDUNE-SP was the first full-scale detector and showed that the technical specifications are accessible.
 Cross section results are currently being finalized.

Detector parameter	ProtoDUNE-SP performance	DUNE specification	
Average drift electric field	500 V/cm	250 V/cm (min)	
		500 V/cm (nominal)	
LAr e-lifetime	> 20 ms	> 3 ms	
TPC+CE			
Noise	(C) 550 e, (I) 650 e ENC (raw)	< 1000 e ENC	
Signal-to-noise (SNR)	(C) 48.7, (I) 21.2 (w/CNR)		
CE dead channels	0.2%	< 1%	
PDS light yield	1.9 photons/MeV	> 0.5 photons/MeV	
	(@ 3.3 m distance)	(@ cathode distance $- 3.6 \text{ m}$)	
PDS time resolution	14 ns	< 100 ns	

JINST 15 P12004